



MATERIAL SAFETY DATA SHEET

PRODUCT: Paste
REVISION NUMBER: 2

REVISION DATE: 04/27/2006
Date Printed: 04/27/2006

1. PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURED BY: Ferro Corporation
251 West Wylie Avenue
P.O. Box 519
Washington, PA 15301
Prod Info 724-223-5900
CHEMTREC 800-424-9300

Use the CHEMTREC telephone number only in the event of chemical emergencies.

PREPARED BY: Mike Pellegrini
Environmental Engineer

PRODUCT CODE: LMM-6046

PRODUCT TRADE NAME: LMM-6046 ANODIZED METAL MARKING SPRAY

CAS NO: Mixture
CHEMICAL FAMILY: Decorative Coating
PRODUCT TYPE: Pigment in Medium

2. COMPOSITION/INFORMATION ON INGREDIENTS

This product does not have exposure limit values. Exposure limit values for some of the components are listed below as a guideline for safe use of this product.

HAZARDOUS COMPONENTS

INGREDIENTS/CAS #	OSHA PEL:	ACGIH TLV:
Vanadium Compound Proprietary	Ceil respirable dust: 0.5 mg/m ³ ; Ceil fume: 0.1 mg/m ³	TWA 0.05 mg/m ³
Crystalline Silica 14808-60-7	TWA respirable dust: 0.1 mg/m ³	TWA respirable dust: 0.05 mg/m ³
Ethyl Alcohol 64-17-5	TWA: 1000 ppm; TWA: 1900 mg/m ³	TWA: 1000 ppm; TWA: 1880 mg/m ³
Methyl Alcohol 67-56-1	TWA: 200 ppm; 260 mg/m ³	TWA: 200 ppm; 262 mg/m ³
Bismuth NONE	NE	NE

3. HAZARDS IDENTIFICATION

PRINCIPLE ROUTES OF EXPOSURE: Inhalation, ingestion and dermal.

PRODUCT TRADE NAME: LMM-6046 ANODIZED METAL MARKING SPRAY

The key immediate hazards are:

Harmful if swallowed
Flammable Liquid
Skin, eye, and respiratory irritant

Effects from Acute Exposure:

EYE CONTACT : Causes eye irritation.

SKIN CONTACT: Causes skin irritation.

INHALATION: Causes lung irritation.

INGESTION: Harmful if swallowed

AGGRAVATED MEDICAL CONDITIONS:

Respiratory

Effects from Chronic Exposure:

CARCINOGENIC INGREDIENTS:

This product contains greater than 0.1% crystalline silica. The International Agency for Research on Cancer (IARC) has determined that "there is sufficient evidence for the carcinogenicity of crystalline silica to experimental animals and limited evidence of carcinogenicity in humans. "The National Toxicology Program (NTP) Sixth Annual Report confirms this determination. It has listed crystalline silica as a substance reasonably anticipated to be a carcinogen.

PRODUCT TRADE NAME: LMM-6046 ANODIZED METAL MARKING SPRAY

OVEREXPOSURE EFFECTS:

CONTAINS CRYSTALLINE SILICA:

Crystalline silica can cause silicosis, a lung disease characterized by coughing, wheezing, impaired lung function and increased sputum production. This damage can be progressive and may cause death. May cause cancer following repeated and prolonged inhalation of the fine dust. Smoking aggravates these effects. Skin and eye contact may cause irritation due to mechanical abrasion.

CONTAINS VANADIUM COMPOUNDS:

Vanadium compounds are highly toxic by inhalation and ingestion. Breathing the dust or fume may cause coughing, rhinitis, bronchitis, metallic taste, and greenish discoloration of the tongue. Skin and eye irritation as well as nausea, vomiting, and diarrhea are also possible. Animal studies have shown this material to cause adverse effects on the male and female reproductive systems, various fertility measures, and the developing fetus.

CONTAINS BISMUTH OXIDE (AS REACTED INTO THE FRIT):

May contain bismuth oxide which has the ability to displace lead from binding sites in the body. This may cause symptoms of lead poisoning (such as abdominal cramps) if a prior history of lead exposure and absorption exists.

CONTAINS DENATURED ALCOHOL:

Overexposure to denatured alcohol can cause serious health effects such as liver toxicity and central nervous system depression ("drunk"). Use during pregnancy may cause fetal alcohol syndrome. Inhalation may cause headache and respiratory irritation. Skin and eye irritant. Denaturants are added to discourage ingestion and will cause nausea and vomiting.

4. FIRST AID MEASURES

INGESTION: If swallowed, give at least 3-4 glasses of water, but do not induce vomiting. Do not give anything by mouth to an unconscious or convulsing person. Get immediate medical attention.

SKIN: For skin contact, wash affected areas with plenty of water, and soap if available, for several minutes. Get medical attention if irritation occurs.

INHALATION: If inhaled, remove from area to fresh air. Get medical attention if respiratory irritation develops or if breathing becomes difficult.

EYES: For eye contact, immediately flush eyes for at least 15 minutes with running water. Hold eyelids apart to ensure rinsing of the entire eye surface and lids with water. Get immediate medical attention if irritation develops.

NOTES TO PHYSICIAN: None specified.

5. FIRE FIGHTING MEASURES

OSHA FLAMMABILITY CLASS: FLAMMABLE

FLASH POINT (°F): 57

Ferro Corporation

PRODUCT TRADE NAME: LMM-6046 ANODIZED METAL MARKING SPRAY

Lower Explosive Limit: Not Available

Upper Explosive Limit: Not Available

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam or Water Mist

FIRE FIGHTING PROCEDURES: Fire-Fighters should wear self-contained breathing apparatus and full protective clothing when fighting chemical fires.

Use water spray to cool nearby containers and structures exposed to fire.

UNUSUAL HAZARDS: Decomposition and combustion products may be toxic.

6. ACCIDENTAL RELEASE MEASURES

SPILL PROCEDURES: Wear appropriate protective equipment. Avoid the generation of dust. Collect material and place in closable container(s) for disposal.

7. HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Avoid contact with eyes, skin and clothing.

NOTES ON HANDLING INFORMATION: Minimize dust generation during handling. Use adequate ventilation.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

VENTILATION: Adequate ventilation should be provided to keep concentrations below acceptable Exposure Limits. Discharge from the ventilation system should comply with the applicable air pollution control regulations.

EYE PROTECTION: Wear safety glasses or goggles to protect against exposure.

PROTECTIVE GLOVES: Use gloves as a standard industrial handling procedure.

RESPIRATORY PROTECTION: Appropriate respiratory protection is required when exposure to airborne contaminant is likely to exceed acceptable limits. Respirators should be selected and used in accordance with OSHA Subpart I (29 CFR 1910.134) and manufacturer's recommendations.

OTHER PERSONAL PROTECTIVE EQUIPMENT: None specified.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Yellow Paste

BOILING POINT: Not Available

VAPOR DENSITY (AIR=1): Heavier than air

PRODUCT TRADE NAME: LMM-6046 ANODIZED METAL MARKING SPRAY

EVAP. RATE(BUTYL ACETATE=1): Slower than n-Butyl Acetate

VOC, Wt.%(EPA METH.24): 32

BULK DENSITY: 15.7 lb/gal

SOLUBILITY (in water): Partially Soluble

10. STABILITY AND REACTIVITY

STABILITY DATA: STABLE

POLYMERIZATION: WILL NOT OCCUR

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide and depending on conditions, some hydrocarbon fragments may also be formed.

INCOMPATIBILITY

(MATERIALS TO AVOID): Strong oxidizing agents

CONDITIONS/HAZARDS TO AVOID: None known.

11. TOXICOLOGICAL INFORMATION

No Toxicological data known.

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: No data at this time

CHEMICAL FATE INFORMATION: No data at this time.

PERSISTENCE/DEGRADABILITY: No data at this time.

APPRAISAL: No data at this time.

MOBILITY: No data at this time.

13. DISPOSAL CONSIDERATIONS

DISPOSAL OF WASTE METHOD: Dispose in accordance with Federal, State and Local regulations.

14. TRANSPORT INFORMATION

DOT Shipping Name: PAINT RELATED MATERIAL

DOT HAZARD CLASS: 3

DOT LABEL(S): FLAMMABLE LIQUID

UN/NA NUMBER: UN1263

PACKING GROUP: PG II

15. REGULATORY INFORMATION

SARA SECTION 302: None Found

PRODUCT TRADE NAME: LMM-6046 ANODIZED METAL MARKING SPRAY

SARA (311, 312) HAZARD CLASS: ACUTE HEALTH HAZARD
CHRONIC HEALTH HAZARD
FIRE HAZARD

SARA 313 Title III Toxic Chemical List:

The following chemicals are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

54	%	Vanadium	8	%
	%	Methanol	1	%
	%	Methyl Isobutyl Ketone	< 1	%

TSCA Inventory Status: This product (and/or all of its components) is in compliance with the U.S. EPA Toxic Substance Control Act, TSCA, (15 U.S.C. 2604).

This product and all of its components is listed on the DSL inventory.

16. OTHER INFORMATION

Revisions: The Format has been changed to meet the requirements of the new ANSI Standard Z400.1.

LABEL INFORMATION:

DANGER!

Flammable liquid.

Contains crystalline silica which can cause lung damage, including cancer.

Harmful if swallowed.

Skin, eye, and respiratory irritant.

Keep away from heat, sparks and flame.

Avoid contact with eyes, skin and clothing.

Do not breathe dust.

Keep away from food products.

Wash thoroughly after handling and before eating, drinking or using cosmetic or tobacco products or toilet facilities.

Use with adequate ventilation.

Keep container closed when not in use.

FIRST AID: If inhaled, remove to fresh air. If breathing is difficult, give oxygen. In case of contact, immediately flush eyes or skin with plenty of water. Remove contaminated clothing. Get medical attention.

IN CASE OF FIRE: Use water, dry chemical or carbon dioxide.

FOR INDUSTRIAL USE ONLY.

IN CASE OF FIRE: Use dry chemical, carbon dioxide, or foam.

PRODUCT TRADE NAME: LMM-6046 ANODIZED METAL MARKING SPRAY

DEFINITIONS AND ABBREVIATIONS :

ACGIH = American Conference of Governmental Industrial Hygienists
C (CEIL) = The concentration that shall not be exceeded during any part of the working exposure.
CAS # = Chemical Abstracts Service Registry Number
EPA = Environmental Protection Agency
IARC = International Agency for Research on Cancer
NIOSH = National Institute for Occupational Safety and Health
NTP = National Toxicology Program
OSHA = Occupational Safety and Health Administration
PEL = Permissible Exposure Limit
SARA = Superfund Amendments and Reauthorization Act
STEL = Short Term Exposure Limit. Usually a 15 minute time weighted average exposure.
TLV = Threshold Limit Values
TSCA = Toxic Substance Control Act
TWA = Time Weighted Average. Exposure concentration for a normal 8 hour day or 40 hour week.
VOC = Volatile Organic Content

DISCLAIMER: The information contained in this Material Safety Data Sheet (MSDS) has been compiled from sources believed to be reliable and to represent the most reasonable current opinion on the subject when the MSDS was prepared. No guarantee is made as to the correctness or sufficiency of the information. The user of this product must decide what safety measures are necessary to safely use this product, either alone or in combination with other products, and determine the regulatory compliance obligations under any applicable federal or state laws.

*** END OF MSDS ***